www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK RELEU TERMIC RTI-1316 9-13A

RTI thermal electrical relay is designed for protecting electric motors from overload, phase unbalance, overcrank condition and rotor jamming. It is installed directly onto KTI and KMI AC contactors. To ensure shortcircuit protection, the unit should be supplied with fuses and modular circuit breakers intended for the correspondent value of rated actuating current. Correspond to the requirements EN 60947-1, EN 60947-4-1, EN 60947-5-1.High accuracy of operation.
Convenient adjustment.
Wide range.Adjustable current range: 9...13
Mounting method: EV008930
Connection type main current circuit: EV000415
Number of auxiliary contacts as normally closed contact: 1
Number of auxiliary contacts as normally open contact: 1
Number of auxiliary contacts as change-over contact: 0
Release class: EV008931
Fuse current aM: 16
Fuse current qG: 25.0
Nominal rated voltage: 230; 400; 600
Rated insulation voltage Ui: 660
Rated surge voltage: 6
Operating frequency: 0-400
Tightening moment: 2
Additional terminal - Tightening torque: 1.2
Additional terminal - Overcurrent protection - pre-ocher gG: 5
Additional terminal - Thermal resistance current In: 5
Ambient temperature: ?? -45 ?? +55
Section of flexible cable connection without tip: 1,5-10
Section of flexible cable connection with tip: 1-4
Width: 44.0

Rigid cable connection section: 1-6
Height: 67.0
Depth: 92.0
Weight: 0,165
Additional terminal - Section of connected conductors: 1,0-1,25
Pret: 47,99 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/releu-termic-rti-1316-9-13a-311855