www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK CONTACT EXTENSIONS PVI-21 DELAY WHEN SELECTOR ING OFF0,1-30 SECONDS 1Z+1P

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. Pneumatic PVI time-delay devices provide for delaying the closing or opening of auxiliary circuits lasting from 0,1 to 180 s. Used in combination with KMI and KTI series of contactors. Correspond to the requirements EN 60947-1, EN 60947-4-1, EN 60947-5-1.High speed response.Type of set-up: EV003970
Contactor design: ??? ????????????? ???, ???
Voltage type for actuating: EV000509
Rated operation current Ie at AC-15, 230 V: 6.0
Rated operation current Ie at DC-13, 230 V: 1.5
Rated control supply voltage Us at AC 50HZ: 660/400/230
Rated control supply voltage Us at DC: 400/220
Number of contacts as normally closed contact: 1
Number of contacts as normally open contact: 1
Time delay range at OFF: 0,1...3,0
Min on capability at min current: 10.0
Min on capability at min voltage: 24.0
Max short-term load: 100.0
Thermal resistance current: 10.0
Insulation resistance: 10.0
Rated insulation voltage Ui: 690
Max. conductor cross section: 2?2,5
Mechanical wear resistance: 1,6?10^6
Degree of protection (IP): EV006405
Operating temperature range: -40...+50
Ambient class: IEK_V0000010
Maintainability: EV000494

Nominal operating DC DC-13 400 V: 0.63
Nominal operating current Ie at AC-15 660 V: 1.50
Nominal operating current Ie at AC-15 400 V: 3.00
Width: 44.0
Height: 50.0
Depth: 58.0
Weight: 0.08
Pret: 84,24 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contact-extensions-pvi-21-delay-when-selector-ing-off0-1-30-seconds-1z-1p-311913