



Nominal operating current  $I_e$  at AC-21 AC-22 230 V: 10  
Nominal operating current  $I_e$  at AC-21 AC-22 400 V: 10  
Nominal operating current  $I_e$  at AC-23 230 V: 7,5  
Nominal operating current  $I_e$  at AC-23 400 V: 7,5  
Nominal operating current  $I_e$  at AC-2 230 V: 7,5  
Nominal operating current  $I_e$  at AC-2 400 V: 7,5  
Nominal operating current  $I_e$  at AC-3 230 V: 5,5  
Nominal operating current  $I_e$  at AC-3 400 V: 5,5  
Nominal operating current  $I_e$  at AC-4 230 V: 1,75  
Nominal operating current  $I_e$  at AC-4 400 V: 1,75  
Rated operation current  $I_e$  at AC-15, 230 V: 2,5  
Nominal operating current  $I_e$  at AC-15 400V: 1,5  
Nominal power at AC-23 230 V: 3/0,8  
Nominal power at AC-23 400 V: 5/1,7  
Nominal power at AC-2 230 V: 2,5  
Nominal power at AC-2 400 V: 3,7  
Nominal power at AC-4 230 V: 0,37  
Nominal power at AC-4 400 V: 0,55  
Nominal power at AC-3 230V: 1,5  
Nominal power at AC-3 400V: 2,2  
Fuse current  $qG$ : 20  
Electric wear resistance: 0,03  
Mechanical wear resistance: 0,1  
Degree of Protection - IP Side of Contacts: EV006404  
Ambient temperature: -25...+40  
Nominal operating voltage AC contacts: 230; 400  
Diameter openings: 7.5  
Nominal Attachment Capacity: 1,5  
Type of switch: EV006495  
Pret: 105,68 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/comutator-cu-came-pkp-10-33-u-10a-1-0-2-3p-400v-311959>