



### **IEK TRANSVERSE ADDITIONAL CONTACT DKP32-20**

Auxiliary contacts of transverse installation DKP32 and simple auxiliary contacts DK32 are intended for boosting the number of supplementary contacts. High speed response. Compatibility: ???32

Nominal rated voltage: 24/48/60/110/230

Number of contacts as change-over contact: 0

Number of contacts as normally open contact: 0

Number of contacts as normally closed contact: 2

Nominal current AC-15 with nominal operating voltage 24V: 2.00

Nominal current AC-15 with nominal operating voltage 48V: 1.25

Nominal current AC-15 with nominal operating voltage 110V: 1.00

Nominal current AC-15 with nominal operating voltage 230V: 0.50

Nominal current DC-13 with nominal operating voltage 48V: 0.30

Nominal current DC-13 with nominal operating voltage 60V: 0.15

Conditional heat current of additional contact: 2.5

Rated insulation voltage  $U_i$ : 250

Rated current DC-13 at rated operating voltage 24V: 1.0

Wear resistance: 10000

Degree of protection (IP): EV006405

Side to join the PRK32: IEK\_V0000373

Type of electric connection: EV000415

Width: 44.5

Height: 11.0

Depth: 28.0

Weight: ? 0,1

Rated operation current  $I_e$  at AC-15, 230 V: 0.5

Mounting method: EV000544

Conductor cross section: 0,75...1,5

Pret: 17,71 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/transverse-additional-contact-dkp32-20-311980>