



### **IEK ADDITIONAL CONTACT DK32-20**

Auxiliary contacts of transverse installation DKP32 and simple auxiliary contacts DK32 are intended for boosting the number of supplementary contacts. High speed response. Compatibility: ???32

Nominal rated voltage: 24/48/110/230/400/660

Number of contacts as change-over contact: 0

Number of contacts as normally open contact: 2

Number of contacts as normally closed contact: 0

Nominal current AC-15 with nominal operating voltage 48V: 6.00

Nominal current AC-15 with nominal operating voltage 110V: 4.50

Nominal current AC-15 with nominal operating voltage 230V: 3.30

Nominal current AC-15 with nominal operating voltage 400V: 2.20

Nominal current AC-15 with nominal operating voltage 660V: 0.60

Nominal current DC-13 with nominal operating voltage 48V: 5.00

Nominal current DC-13 with nominal operating voltage 110V: 0.30

Nominal current DC-13 with nominal operating voltage 230V: 0.50

Conditional heat current of additional contact: 6.0

Rated insulation voltage  $U_i$ : 690

Rated current DC-13 at rated operating voltage 24V: 6.0

Wear resistance: 10000

Degree of protection (IP): EV006405

Side to join the PRK32: IEK\_V0000366

Type of electric connection: EV000415

Width: 9.0

Height: 91.0

Depth: 67.0

Weight: ? 0,1

Rated operation current  $I_e$  at AC-15, 230 V: 3.3

Mounting method: EV003965

Conductor cross section: 0,75...1,5  
Pret: 47,24 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/additional-contact-dk32-20-311982>