





IEK SIGNAL-ADDITIONAL CONTACT DK/AK32-02

Auxiliary and signal auxiliary contacts in one case DK/AK32 are designed for boosting the number of supplementary contacts and overcurrent tripping alarm PRK32. Remote alarm notification and status

monitoring.Compatibility: ???32

Nominal rated voltage: 24/48/60/110/230 Number of contacts as change-over contact: 0 Number of contacts as normally open contact: 0 Number of contacts as normally closed contact: 2

Nominal current AC-15 with nominal operating voltage voltage 24V: 1.50

Nominal current AC-15 with nominal operating voltage 48V: 1.00 Nominal current AC-15 with nominal operating voltage 110V: 0.50 Nominal current AC-15 with nominal operating voltage 230V: 0.30 Nominal current DC-13 with nominal operating voltage 48V: 0.30 Nominal current DC-13 with nominal operating voltage 60V: 0.15

Conditional heat current of additional contact: 6.0 Conditional heat current of emergency contact: 2.5

Rated insulation voltage Ui: 690

Rated current DC-13 at rated operating voltage 24V: 1.0

Wear resistance: 10000

Degree of protection (IP): EV006405 Side to join the PRK32: IEK_V0000366 Type of electric connection: EV000415

Width: 9.0 Height: 91.0 Depth: 67.0 Weight: ? 0,1

Rated operation current Ie at AC-15, 230 V: 0.3

Mounting method: EV003965

Conductor cross section: 0,75...1,5

Pret: 45,28 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/signal-additional-contact-dk-ak32-02-311984