

IEK PUSH-BUTON CONTROL DESK PKT -62 PENTRU 4 BUTON S IP54

Push-button control desk is intended for commuting electric circuits controlling hoisting mechanisms. They represent a sealed casing made of thermal-resistant ABS-plastic with buttons. To ensure sealing of the cable lead-in a protective gland is provided. There is an O-ring mounted between the casing and the keyboard. According to its constructive and technical features, PKT series talfer button keyboards meet the requirements of IEC 60947-5-1.Option of installing 2, 4 or 6 buttons.
PKT casing is made of ABS-plastic being a non-flammable material.
Protective gland at the cable lead-in excludes dust and moisture ingress.Number of command positions: 4
Number of speeds: 1
Type of executable motions: EV000154
Material housing: EV000139
Width: 68
Height: 50
Depth: 273
Nominal voltage: 400
Frequency: EV008013
Ambient temperature: -25...+45
Functions of control buttons: IEK_V0000410
Conventional thermal current under cover I the: 5
Nominal rated voltage: 120/230/400
Nominal operating current Ie at AC-15 120 V: 6.0
Rated operation current Ie at AC-15, 230 V: 3.0
Nominal operating current Ie at AC-15 400V: 1.5
Switch on and off ability: 10
Rated insulation voltage Ui: 500
Switching overvoltage: 500
Rated surge voltage invariability: 4
Nominal conditional short-circuit current Icn: 1000

Protection against short-circuit current at Ie 3A pre-cover qG: 5.0
Protection against short-circuit current at Ie 1_5A pre-cover qG: 3.0
Model: IEK_V0000412
Presence of lock: IEK_V0000413
Actuating force: 30
Mechanical wear resistance: 30000
Degree of protection (IP): EV006419
Section of the connected conductors: ? 1,5
Application in the environment: IEK_V0000414
Internal size for cable: 12
Length: 173
Pret: 73,56 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/push-buton-control-desk-pkt-62-pentru-4-buton-s-ip54-312243