



IEK PUSH-BUTON CONTROL DESK PKT -62 PENTRU 4 BUTON S IP54

Push-button control desk is intended for commuting electric circuits controlling hoisting mechanisms. They represent a sealed casing made of thermal-resistant ABS-plastic with buttons. To ensure sealing of the cable lead-in a protective gland is provided. There is an O-ring mounted between the casing and the keyboard. According to its constructive and technical features, PKT series talfer button keyboards meet the requirements of IEC 60947-5-1. Option of installing 2, 4 or 6 buttons.

PKT casing is made of ABS-plastic being a non-flammable material.

Protective gland at the cable lead-in excludes dust and moisture ingress. Number of command positions: 4

Number of speeds: 1

Type of executable motions: EV000154

Material housing: EV000139

Width: 68

Height: 50

Depth: 273

Nominal voltage: 400

Frequency: EV008013

Ambient temperature: -25...+45

Functions of control buttons: IEK_V0000410

Conventional thermal current under cover I the: 5

Nominal rated voltage: 120/230/400

Nominal operating current Ie at AC-15 120 V: 6.0

Rated operation current Ie at AC-15, 230 V: 3.0

Nominal operating current Ie at AC-15 400V: 1.5

Switch on and off ability: 10

Rated insulation voltage Ui: 500

Switching overvoltage: 500

Rated surge voltage invariability: 4

Nominal conditional short-circuit current Icn: 1000

Protection against short-circuit current at Ie 3A pre-cover qG: 5.0

Protection against short-circuit current at Ie 1_5A pre-cover qG: 3.0

Model: IEK_V0000412

Presence of lock: IEK_V0000413

Actuating force: 30

Mechanical wear resistance: 30000

Degree of protection (IP): EV006419

Section of the connected conductors: ? 1,5

Application in the environment: IEK_V0000414

Internal size for cable: 12

Length: 173

Pret: 72,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/push-butan-control-desk-pkt-62-pentru-4-butan-s-ip54-312243>