www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK SELECTOR ANC-22-2 2 FIXED POSITIONS RED NEON /240V I-O 1C+1R

Control buttons and switches are designed for an operative management of contactors (automatic tripping contactors) and automatics relay within AC electric circuits of 50 Hz and voltage limited to 600 V or DC circuits limited to 400 V and other technological processes. Various color variants provide for the most efficient arrangement of panels and boards. All devices consist of two units: removable head and contact module. Black NO contact block (1NO) and brown NC unit (1NC).Low cost, high reliability and ease of installation.
The wide range allows to complete a case of any complexity.Number of poles: 1
Max. rated operation voltage Ue AC: 660
Rated permanent current Iu: 7.5
Number of switch positions: 2
Device construction: EV002104
Type of control element: EV004094
Degree of protection (IP), front side: EV006415
Number of auxiliary contacts as normally open contact: 1
Connection type main current circuit: EV000415
Number of auxiliary contacts as normally closed contact: 1
Rated insulation voltage Ui: 660
Nominal heat current Th: 10
Rated operation current Ie at AC-15, 230 V: 7,5
Nominal operating current Ie at AC-15 400V: 4,5
Electric wear resistance: 0,3
Degree of Protection - IP Side of Contacts: EV006404
Ambient temperature: -10...+40
Nominal operating voltage AC contacts: 110; 230; 400; 660
Nominal operating voltage DC contacts: 24; 48; 110; 220; 440
Diameter openings: 22.0
Nominal voltage DC: 440

Nominal Attachment Capacity: 2?2,5
Width: 30.0
Height: 48.0
Depth: 86.0
Type of switch: EV009208
Pret: 21,20 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/selector-anc-22-2-2-fixed-positions-red-neon-240v-i-o-1c-1r-312249