



### **IEK SELECTOR LAY5-BJ33 3 POSITIONS "I-0-II" LONG HANDLE**

Control buttons and switches are designed for an operative management of contactors (automatic tripping contactors) and automatics relay within AC electric circuits of 50 Hz and voltage limited to 600 V or DC circuits limited to 400 V and other technological processes. Various color variants provide for the most efficient arrangement of panels and boards. All devices consist of two units: removable head and contact module. Black NO contact block (1NO) and brown NC unit (1NC). Low cost, high reliability and ease of installation.

The wide range allows to complete a case of any complexity. Number of poles: 1

Max. rated operation voltage  $U_e$  AC: 600

Rated permanent current  $I_u$ : 7.5

Number of switch positions: 3

Device construction: EV002104

Type of control element: EV004095

Degree of protection (IP), front side: EV006415

Connection type main current circuit: EV000415

Rated insulation voltage  $U_i$ : 600

Nominal heat current  $I_{th}$ : 10

Rated operation current  $I_e$  at AC-15, 230 V: 3,0

Nominal operating current  $I_e$  at AC-15 400V: 1,5

Degree of Protection - IP Side of Contacts: EV006405

Ambient temperature: -10...+40

Nominal operating voltage AC contacts: 110; 230; 400; 600

Nominal operating voltage DC contacts: 24; 48; 110; 220; 400

Diameter openings: 22.0

Nominal voltage DC: 400

Nominal Attachment Capacity: 2?2,5

Width: 45.0

Height: 29.5

Depth: 69.0

Type of switch: EV006495

Pret: 22,67 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/selector-lay5-bj33-3-positions-i-0-ii-long-handle-312270>