



IEK NPISH1,5-2,5 ALBASTRU (100PCS.)

Insulated round pin tips (NkISH) and flat ones (NpISH) are designed for terminating the copper multi-wire conductors used in various control devices and systems that require rapid circuit switching. With these conductors it is performed the connection of the TE, TEM and TO timers and modular control buttons CMU 11 TM IEK as well. There are several ways of fixing the tips: screw clamp, spring clamp, etc. Depending on the shape and design of the contact terminal and functional requirements, the preference may be given to one or another modification of the pin tips. Depending on the shape and device of the contact terminal and the functional requirements, preference may be given to one or another modification of the pin tips.

Easy to attach timers, modular control buttons.

Alternative to sleeve tips-sleeves with a difference in the method of crimping.

3 sizes of pin lugs can replace 9 sizes of sleeve-type.Length of a connecting part: 9.0

Ambient class: IEK_V0000067

Max diameter of a cable on isolation: 5.0

Material insulation: EV000163

Material: EV000138

Bolt dimension metric (M.): -

Nominal voltage: 400

Nominal cross section: 1,5...2,5

Nominal rated current: 27

Total length: 19.5

Ambient temperature: -10...75

Flange shape: EV014437

Colour insulation: EV000080

Pret: 22,91 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/npish1-5-2-5-albastru-100pcs-312663>