

IEK PINI WITH BOLT NS -625 35 KW

The bolted terminals and sleeves, like compression terminals and sleeves, are designed for termination of conductors. However they can be fixed without use of expensive equipment. A torque wrench is sufficient. Moreover, their unquestionable advantage is a capability to be used for termination and connection of both copper and aluminum conductors. All products have conductivity according to GOST 17441-84.At the tips of BL (bolted lug) break bolts are located in different planes at an angle of 180° to each other. In comparison with the location of the bolts on one side, the clamping of the cable core on different sides provides a more secure fixation of the conductor and increases the spot of electrical contact. Depending on the cross section of the vein, the number of bolts varies from 5 to 10.
All bolted terminals and connectors are marked indicating the allowable cable cross sections and manufacturer's code.Weight: 0,65
Height: 55.5
Length: 175.0
Surface protection: EV000899
Number of screws: 5
Material: IEK_V0000333
Bolt dimension metric (M..): 20?1,5
Moment of screw head failure during installation of line cabs: 62,2
Nominal cross section: 625
Operating voltage: 35000
Ambient temperature: -60...+80
Cross section form: EV010032
Colour insulation: EV000154
Width: 52.0
Pret: 419,98 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/pini-with-bolt-ns-625-35-kw-312798