www.MATERIALE ELECTRICE.ro
Consiliere specializata



# IEK CLEME DE CAPAT KZVI 16MM2 (5X1)

IEK screw terminal KZVI is used for screw connection of conductors, protecting the wire from damage and eliminating the possibility of a short circuit to the electrical installation case.CSVI housing is fully protected against short-circuit screw contact groups with each other or the metal housing plug-in electrical products. The screw connection is vibration resistant.
The connection of cables and wires with the help of CSVI allows you to securely fix several wires together.Connectable conductor cross section fine-strand without cable end sleeve: 2?16
Connectable conductor cross section solid-core: 2?16
Connectable conductor cross section multi-wired: 2?16
Rated current In: 75
Nominal rated voltage: 450
Type of electrical connection 2: EV000415
Connection position: EV000644
Number of poles: 1
Number of clamp positions per pole: 1
Mounting method: EV005276
Material insulation body: EV000154
Operation temperature: -25...+85
Width/grid dimension: 22.5
Height at lowest possible mounting height: 33
Length: 31
Colour: EV000154
Nominal operating AC voltage Ue: 450
Nominal DC operating voltage Ue: 450
Nominal frequency: 50
Rated insulation voltage Ui: 500
Max. conductor cross section: 2?16
Material clamp: EV000149

Ambient class: IEK_V0000067
Degree of protection (IP): EV006405
Width: 22,5
Height: 32,7
Nominal Attachment Capacity: 2?6...2?16
Allowable long-term current: 75
Tightening torque Nm at conductor section: 3,5
Max operating voltage Ue: 450
Quantity in the kit: 5
Type of electrical connection 1: EV000415
Pret: 17,48 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/cleme-de-capat-kzvi-16mm2-5x1-312993