www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK TERMOCONTRACTIBIL TTU 14/7 ALB 1 M

The heat-shrink tubes from thin polyethylene are halogen-free and have fire suppression property. The products have good electrical and mechanical properties and are used as insulating and sealing materials. Being heated after putting in stretched state on various items, they shrink and fit close to an item, assuming its shape. The heat-shrink tubes have the following color options: white, yellow, green/yellow, green, red, blue and black.A wide range of different tube diameters for working with conductors of different sections. The material of the tubes does not contain halogens and are flame-retardant.Model: EV009713
Inner diameter before heat-shrink: 14
Inner diameter after heat-shrink: 7
Colour: EV000202
Nominal cross section: 13
Material: EV003904
Shrink rate: EV009534
Wall thickness after shrinking: 0,7±0,1
Length: 1
Operation temperature: -55...125
Mounting temperature: -10...50
AC 50 Hz operating voltage: 660
Tensile strength: ? 10,4
Volumetric electrical resistance: ? 1?10^14
For dielectric strength up to: ? 15
Min shrinkage start temperature: 70
Min full shrinkage temperature: 125
Wall thickness before heat shrinkage: 0,35±0,1
Wire Diameter Range: 7,3...13,0
Type: EV004267
Pret: 3,77 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/termocontractibil-ttu-14-7-alb-1-m-313085