



**SCHNEIDER PRIZA, NEW UNICA, PRODUS COMPLET, 2P E, 16A, SCHUKO, CU  
OBTURATSAU, IP44, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU003718 is a complete product in color white. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the German standard. The dielectric strength of this socket-outlet is 2000V. Its rated current is 16A. The fixing mode of this device is screws. It is 90 mm in width and 80 mm in height. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. With IP44 level reached, the device has better performance against solid particle and liquid. It reaches IK04 protection level, which can help protect against impact. Its connection terminals are screw terminals. The socket-outlet is made of PC, making it resistant and durable. This cover plate is AENOR, EAC certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Complete product

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules  
Fixing mode - Screws  
Colour tint - White (RAL 9003)  
Connections - terminals - Screw terminals  
Cable cross section -  $0.4 \text{ mm}^2$  cable(s), 2 - cable stiffness: flexible  
 $0.4 \text{ mm}^2$  cable(s), 2 - cable stiffness: rigid  
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un,  $\cos \phi = 0.6$   
Electrical durability - 10000 cycles,  $\cos \phi = 0.8$   
Insulation resistance -  $> 5 \text{ M}\Omega$  at 500 V  
Dielectric strength - 2000 V  
Material - PC: mechanism cover  
Surface finish - Glossy  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
UNE 20315-1-1  
UNE 20315-1-2  
DIN VDE 0620-1  
Product certifications - AENOR  
EAC  
Embedding depth - 30.5 mm  
Depth - 52.6 mm  
Width - 90 mm  
Height - 80 mm  
Surface treatment - Untreated  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation -  $-5 \text{ to } 35 \text{ }^\circ\text{C}$   
Ambient air temperature for storage -  $-5 \text{ to } 50 \text{ }^\circ\text{C}$   
IK degree of protection - IK04  
IP degree of protection - IP44  
Environmental characteristic - Acetone  
Bleach  
UV resistant  
Petrol  
Oil  
Alcohol  
Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 5.3 cm  
Package 1 Width - 9 cm  
Package 1 Length - 9 cm  
Package 1 Weight - 83 g

Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 5  
Package 2 Height - 8.2 cm  
Package 2 Width - 19.7 cm  
Package 2 Length - 22.6 cm  
Package 2 Weight - 520 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 60  
Package 3 Height - 30 cm  
Package 3 Width - 40 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 7.01 kg  
Pret: 57,10 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-produs-complet-2p-e-16a-schuko-cu-obturatsau-ip44-lucios-netratat-alb-316544>