



COMTEC MOTOR STARTERE ECHIPATE CU RELEE TERMICE SI BOBINE DE 400V **MARIMEA 1 4.00-6.00A 18A**

Standard: EN 50298; EN060529; EN 50274

Temperatura mediului: – 5...+ 40 grade C

Anduranta: > 1.500.000 cicluri la I=ITH

Tip constructiv: marimile 1 si 2 – policarbonat ignifugat; marimea 3 – metal

Conductor racord: identic cu cel de la contactoare in functie de marimea fiecaruia

Montaj: pe perete cu dibluri si holtsuruburi

Borne de legatura: cu surub si saiba profilata pentru doua conductoare

Releu termic: marimea 1 si 2 – LR2-D13...; marimea 3 – LR
-D33..

Reglajul domeniului: marimea 1 si 2: 0.4-0.63; 0.63-1; 1-1.6; 1.6-2.5; 2.5-4; 4-6; 5.5-8; 7-10; 9-13; 12-18;
17-25; 25-32;

: marimea 3: 23-32; 37-50; 55-70; 63-80; 80-93

Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/motor-startere-echipate-cu-relee-termice-si-bobine-de-400v-marimea-1-4-00-6-00a-18a-317199>