



SCHNEIDER PRIZA DUBLA, NEW UNICA, COMPLETE PRIZA, 2P, 16A, EUROPEAN, CU OBTURATSAU, IP4X, LUCIOS, NETRATAT, ALB

Schneider Electric New Unica socket-outlet NU206318 is a complete socket-outlet in color white with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. This device respects the European standard. The dielectric strength level, namely the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown or electrical discharge, is 2000V. Its rated current is 16A. The fixing mode of this device is screws. It is 85 mm in width, It is 125 mm in height, 47 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. this cover plate is AENOR, EAC, NF certified. Being environmentally friendly, this socket-outlet is a green premium product. It is mercury free as well as heavy metal free, taking care of the environment. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Range - New Unica

Product or component type - Socket-outlet aesthetic name - Unica Studio device presentation - Complete socket-outlet device mounting - Flush Socket number - 2 Outlet poles configuration - 2P Outlet standard deviation - European Rated current - 16 A Complementary Device application - Power supply Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Screws

Colour tint - White (RAL 9003)

Connections - terminals - Screw terminals

Cable cross section - 0a€|2.5 mmA² cable(s), 2 - cable stiffness: flexible

0a€|2.5 mmA² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, $\cos phi = 0.6$

Electrical durability - 10000 cycles, $\cos phi = 0.8$

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

Surface finish - Glossy

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

NF C 61-314

Product certifications - AENOR

EAC

NF

Embedding depth - 24 mm

Depth - 47 mm

Width - 85 mm

Height - 125 mm

Net weight - 0.099 kg

Surface treatment - Untreated

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5a€|35 A°C

Ambient air temperature for storage - -5a€|50 A°C

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil

Alcohol

Window-cleaning fluid

Liquid soap

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 5 cm

Package 1 Width - 8.5 cm

Package 1 Length - 12.6 cm

Package 1 Weight - 90 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5

Package 2 Height - 12.5 cm

Package 2 Width - 17.5 cm

Package 2 Length - 26 cm

Package 2 Weight - 584 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 45

Package 3 Height - 30 cm

Package 3 Width - 40 cm

Package 3 Length - 60 cm

Package 3 Weight - 6.02 kg

Pret: 44,11 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/priza-dubla-new-unica-complete-priza-2p-16a-european-cu-obturatsau-ip4x-lucios-netratat-alb-318748