



**SCHNEIDER PRIZA DUBLA, NEW UNICA, COMPLETE PRIZA, 2P, 16A, EUROPEAN,
CU OBTURATSAU, IP4X, LUCIOS, NETRATAT, BEJ**

Schneider Electric New Unica socket-outlet NU206344 is a complete socket-outlet in color beige with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. And this device is European standard. The dielectric strength of this socket-outlet is 2000V. Its rated current is 16A. Screws this socket-outlet for the fixation. It is 85 mm in width, 125 mm in height and 47 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. The socket-outlet is made of PC, making it resistant and durable. It obtained AENOR, EAC, NF certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

aesthetic name - Unica Studio

device presentation - Complete socket-outlet

device mounting - Flush

Socket number - 2

Outlet poles configuration - 2P

outlet standard - European

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz
Fixing mode - Screws
Colour tint - Beige (RAL 1013)
Connections - terminals - Screw terminals
Cable cross section - 0a€12.5 mmA² cable(s), 2 - cable stiffness: flexible
0a€12.5 mmA² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
Surface finish - Glossy
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
UNE 20315-1-1
UNE 20315-1-2
NF C 61-314
Product certifications - AENOR
NF
EAC
Embedding depth - 24 mm
Depth - 47 mm
Width - 85 mm
Height - 125 mm
Net weight - 0.099 kg
Surface treatment - Untreated
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5a€135 A°C
Ambient air temperature for storage - -5a€150 A°C
IK degree of protection - IK04
IP degree of protection - IP4X
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.7 cm
Package 1 Width - 8.5 cm

Package 1 Length - 12.6 cm
Package 1 Weight - 95 g
Unit Type of Package 2 - CAR
Number of Units in Package 2 - 5
Package 2 Height - 12 cm
Package 2 Width - 17.5 cm
Package 2 Length - 26 cm
Package 2 Weight - 610 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 45
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 6.28 kg
Pret: 36,33 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-dubla-new-unica-complete-priza-2p-16a-european-cu-obturatsau-ip4x-lucios-netratat-bej-318749>