

SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P, 10A, EUROPEAN, CU OBTURATSAU, IP3X, VOPSIT, ANTRACIT

Schneider Electric New Unica socket-outlet NU303154 is a mechanism in color anthracite. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. And this device is European standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 10A. The fixing mode of this device is clip-in. It is 22.5 mm in width, 45 mm in height and 39.3 mm in depth with an embedding depth of 30 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It benefits from an elegant matt finishing, constituting an added-value for your interior design. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. Its connection terminals are screw terminals. The socket-outlet is made of Cu.Zn37, PC (polycarbonate) GF10 FR, making it as resistant as possible. It obtained EAC certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main
Range - New Unica
Product or component type - Socket-outlet
device presentation - Mechanism
device mounting - Flush
Socket number - 1
Outlet poles configuration - 2P
outlet standard - European
Rated current - 10 A
Complementary
Device application - Power supply
Cover type - With shutter
[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz

Number of modules - 1 module
Fixing mode - Clip-in
Colour tint - Anthracite (RAL 7021)
Connections - terminals - Screw terminals
Cable cross section - 0a€¦4 mmA² cable(s), 2 - cable stiffness: flexible
0a€¦4 mmA² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
CuZn37: terminals
Surface finish - Painted
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
UNE 20315-1-1:1994
Product certifications - EAC
Embedding depth - 30 mm
Depth - 39.3 mm
Width - 22.5 mm
Height - 45 mm
Net weight - 0.019 kg
Surface treatment - Painted
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5a€¦35 A°C
Ambient air temperature for storage - -5a€¦50 A°C
IK degree of protection - IK04
IP degree of protection - IP3x
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 2.5 cm
Package 1 Width - 4.0 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 19.0 g

Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 5.5 cm
Package 2 Width - 14.0 cm
Package 2 Length - 26.0 cm
Package 2 Weight - 190.0 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 100
Package 3 Height - 30.0 cm
Package 3 Width - 30.0 cm
Package 3 Length - 40.0 cm
Package 3 Weight - 2.39 kg
Pret: 36,67 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/priza-new-unica-mecanism-2p-10a-european-cu-obturatsau-ip3x-vopsit-antracit-318756