

SCHNEIDER PRIZA DUBLA, NEW UNICA, MECANISM, 2P E, 16A, SCHUKO, CU OBTURATSAU, TERMINAL FARA SURUBURI, VOPSIT, ANTRACIT

Schneider Electric New Unica socket-outlet NU306654 is a mechanism in color anthracite with 2 socket outlets.. This socket-outlet is 2 x 2P with shutters. And this device is German standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 16A. Clip-in this socket-outlet for the fixation. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is brilliant, gaining extra point for your interior design. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. Its connection terminals are screwless terminals. The socket-outlet is made of PC, making it resistant and durable. This socket-outlet is DEMKO, EAC, SEMKO certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main
Range - New Unica
Device application - Power supply
Product or component type - Socket-outlet
device presentation - Mechanism
Socket number - 2
Outlet poles configuration - 2P + E
outlet standard - Schuko
Outlet standard description - Side earth
Ground lug position - 45A° ground lug
Condition of use - Indoor
Complementary
Cover type - With shutter
device mounting - Flush
Rated current - 16 A
[Ue] rated operational voltage - 250 V

Network type - AC
Network frequency - 50/60 Hz
Number of modules - 4 modules
Fixing mode - Clip-in
Colour tint - Anthracite (RAL 7021)
Connections - terminals - Screwless terminals
Cable cross section - 0a€¦2.5 mmA² cable(s), 2 - cable stiffness: flexible
0a€¦2.5 mmA² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
Surface finish - Painted
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
Product certifications - SEMKO
DEMKO
EAC
Embedding depth - 31.1 mm
Depth - 40.4 mm
Width - 45 mm
Height - 90 mm
Net weight - 0.077 kg
Surface treatment - Painted
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5a€¦35 A°C
Ambient air temperature for storage - -5a€¦50 A°C
IK degree of protection - IK04
IP degree of protection - IP21D
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.35 cm
Package 1 Width - 4.5 cm
Package 1 Length - 9 cm

Package 1 Weight - 66 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 7.5 cm
Package 2 Width - 21.5 cm
Package 2 Length - 27 cm
Package 2 Weight - 805 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 90
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 7.948 kg
Pret: 61,42 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/priza-dubla-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-terminal-fara-suruburi-vopsit-antracit-318868