



SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, ITALIAN, CU
OBTURATSAU, LUCIOS, NETRATAT, ALB

Schneider Electric New Unica socket-outlet NU302318 is a mechanism in color white. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is Italian standard. The dielectric strength level, namely the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown or electrical discharge, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 22.5 mm in width, 45 mm in height, 33 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is brilliant, gaining extra point for your interior design. The IP rating of this device is IP20. It reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. this cover plate is FR.ME63.B02375 AC certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Italian

Outlet standard description - Centred earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz
Number of modules - 1 module
Fixing mode - Clip-in
Colour tint - White (RAL 9003)
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm² cable(s), 2 - cable stiffness: flexible
0.4 mm² - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
Surface finish - Glossy
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
Embedding depth - 24 mm
Depth - 35.5 mm
Width - 22.5 mm
Height - 45 mm
Net weight - 0.0275 kg
Surface treatment - Untreated
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5 to 35 A°C
Ambient air temperature for storage - -5 to 50 A°C
IK degree of protection - IK01
IP degree of protection - IP21D
Environmental characteristic - Bleach
Liquid soap
Acetone
Window-cleaning fluid
Alcohol
Petrol
Oil
UV resistant
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 2 cm
Package 1 Width - 3.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 28 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10

Package 2 Height - 7 cm
Package 2 Width - 12 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 345 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 160
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 5.908 kg
Pret: 22,67 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-e-16a-italian-cu-obturatsau-lucios-netratat-alb-318891>