



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, ITALIAN, CU  
OBTURATSAU, LUCIOS, NETRATAT, BEJ**

Schneider Electric New Unica socket-outlet NU302344 is a mechanism in color beige. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the Italian standard. The dielectric strength, a measure of the electrical strength of a material as an insulator, is 2000V. Its rated current is 16A. Clip-in this socket-outlet for the fixation. It is 22.5 mm in width, 45 mm in height, 33 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It reaches IP20 degree of protection which is very high. Besides, it reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. Being made of ASA + PC material, this socket-outlet is quite reliable and resistant. It obtained FR.ME63.B02375 AC certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main  
Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Italian

Outlet standard description - Centred earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz  
Number of modules - 1 module  
Fixing mode - Clip-in  
Colour tint - Beige (RAL 1013)  
Connections - terminals - Screw terminals  
Cable cross section -  $0.4 \text{ mm}^2$  cable(s), 2 - cable stiffness: flexible  
 $0.4 \text{ mm}^2$  - cable stiffness: rigid  
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un,  $\cos \phi = 0.6$   
Electrical durability - 10000 cycles,  $\cos \phi = 0.8$   
Insulation resistance -  $> 5 \text{ MOhm}$  at 500 V  
Dielectric strength - 2000 V  
Material - PC: mechanism cover  
PC (polycarbonate) GF10 FR: casing  
Surface finish - Glossy  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
Embedding depth - 24 mm  
Depth - 35.5 mm  
Width - 22.5 mm  
Height - 45 mm  
Net weight - 0.0275 kg  
Surface treatment - Untreated  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation -  $-5 \text{ to } 35 \text{ A}^\circ\text{C}$   
Ambient air temperature for storage -  $-5 \text{ to } 50 \text{ A}^\circ\text{C}$   
IK degree of protection - IK01  
IP degree of protection - IP21D  
Environmental characteristic - Acetone  
Window-cleaning fluid  
UV resistant  
Liquid soap  
Petrol  
Alcohol  
Oil  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 3.55 cm  
Package 1 Width - 2.25 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 27.5 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10

Package 2 Height - 6.5 cm  
Package 2 Width - 12 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 343.3 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 160  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 5.934 kg  
Pret: 28,06 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-e-16a-italian-cu-obturatsau-lucios-netratat-bej-318893>