



SCHNEIDER CONNECTED SINGLE PRIZA, NEW UNICA, 16 A, PIN, ALUMINIU

This Schneider Electric Wiser New Unica connected schuko socket outlet with shutter ensuring safety protection with earthing pin. This device respects the German standard. The operating voltage is 250VAC 50/60Hz. Its rated current is 16A. The dielectric strength, a measure of the electrical strength of a material as an insulator, is 2000V. Easy installation, screwdriver is not required to connect the cables, thanks to the screwless connection. The dimension of the product is (W) 74.5mm x (H) 74.5mm x (D) 40mm. The Embedded depth is 30.5mm. The socket outlet is made of PC material. And the color of the product is Aluminium with a glossy finish. It is compatible with ambient air temperature for operation between 5A°C to 35A°C. It reaches IP20 and IK05 degrees of protection. Delivered in set of 1 Box packaging. To be completed with the cover frame. The device is fixed with 4 fixing points. New Unica is designed with clever features to be flexible, easy to understand, and quick to install providing solutions for all customer's requirements. It is designed for sustainable living in environmentally conscious households. New Unica includes a suite of new designs, colors, and materials. Users benefit from beautiful designs that match their style and innovative products. This device is compliant with NF certification.

Range - New Unica

Device application - Power supply

Product or component type - Connected socket-outlet

device presentation - Mechanism with zamak fixing frame

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - French

Outlet standard description - Pin earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz
Number of modules - 2 modules
Fixing mode - 4 fixing points
Colour tint - Aluminium
Connections - terminals - Screwless terminals
Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible
0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 I_n and 1.1 I_{un}, cos φ = 0.6
Electrical durability - 10000 cycles, cos φ = 0.8
Insulation resistance - > 5 MΩ at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
Zamak: fixing frame
PC (polycarbonate) GF10 FR: casing
Surface finish - Painted
Quantity per set - Set of 1 box
Standards - IEC 60884-1
NF C 61-314
Product certifications - NF
Embedding depth - 30.5 mm
Depth - 40 mm
Width - 74.5 mm
Height - 74.5 mm
Net weight - 0.0739 kg
Surface treatment - Painted
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5-35 °C
Ambient air temperature for storage - -5-50 °C
IK degree of protection - IK05
IP degree of protection - IP20
Environmental characteristic - Acetone
UV resistant
Petrol
Oil
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.7 cm
Package 1 Width - 9.5 cm
Package 1 Length - 9.5 cm
Package 1 Weight - 162.0 g
Unit Type of Package 2 - S03

Number of Units in Package 2 - 36

Package 2 Height - 30.0 cm

Package 2 Width - 30.0 cm

Package 2 Length - 40.0 cm

Package 2 Weight - 6.273 kg

Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/connected-single-priza-new-unica-16-a-pin-aluminiu-318939>