



**SCHNEIDER FRENCH PRIZA, NEW UNICA, 2PE, 16 A , SCL, SURGE PROTECTION, ALB**

Schneider Electric New Unica socket-outlet NU305918EP is a mechanism in color white. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is French standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 16A. Clip-in this socket-outlet for the fixation. It is 45 mm in width, 45 mm in height 38 mm in depth with an embedding depth of 28.7 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screwless terminals connection terminals. Being made of PC material, this socket-outlet is quite reliable and resistant. This socket-outlet is NF certified. As a green premium product, this device is environmentally friendly. It is mercury free. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

aesthetic name - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

Outlet poles configuration - 2P + E with shutters

Outlet standard - French

Outlet standard description - Pin earth

Cover plate colour tint - White

White (RAL 9003)

Quantity per set - 1 box

Complementary

Protection type - Overvoltage protection

Rated current - 16 A at 230 V AC 50/60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Pilot light - LED, colour: green and red

Connections - terminals - Screwless terminals

Cable cross section - 4 mm<sup>2</sup> flexible cable

0a€|2.5 mm<sup>2</sup> flexible cable

4 mm<sup>2</sup> rigid cable

0a€|2.5 mm<sup>2</sup> rigid cable

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MOhm at 500 V

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Embedding depth - 36.7 mm

Depth - 45.45 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.044 kg

Environment

Dielectric strength - 2000 V

Standards - IEC 60884-1

Product certifications - CE

Ambient air temperature for operation - -5a€|35 A°C

Ambient air temperature for storage - -5a€|50 A°C

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Acetone

Liquid soap

Oil

Petrol

UV resistant

Bleach

Window-cleaning fluid

Alcohol

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 6.3 cm

Package 1 Width - 7.7 cm

Package 1 Length - 8.6 cm

Package 1 Weight - 72.9 g

Unit Type of Package 2 - S03

Number of Units in Package 2 - 57

Package 2 Height - 30 cm

Package 2 Width - 30 cm

Package 2 Length - 40 cm

Package 2 Weight - 4.596 kg

Unit Type of Package 3 - P06

Number of Units in Package 3 - 456

Package 3 Height - 77 cm

Package 3 Width - 60 cm

Package 3 Length - 80 cm

Package 3 Weight - 45.27 kg

Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/french-priza-new-unica-2pe-16-a-scl-surge-protection-alb-318945>