



SCHNEIDER BUTON DUBLU, NEW UNICA, 1-POLE 2-WAY, 10AX, 2 MODULE, TERMINAL FARA SURUBURI, VOPSIT, IP4X, ANTRACIT

Schneider Electric New Unica switch NU321354 is a mechanism in color anthracite with 2 rockers. This is a double one-way switch. The fixing mode of this device is clip-in. Its rated current is 10AX. It is 45 mm in width, It is 45 mm in height, 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. This switch has screwless terminals connection terminals. Cu.Zn37, PBT (polybutylene terephthalate) GF30, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized It obtained AENOR, CE, EAC, NF certificate. Being environmentally friendly, this switch is a green premium product. It is mercury free.as well as heavy metal free, taking care of the environment and your health. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica
Product or component type - Switch
device presentation - Mechanism
Technology type - Electromechanical
Switch function - 1-pole 2-way
Number of rocker - 2
Device application - Light control
Colour tint - Anthracite (RAL 7021)
Type of packing - Flow-pack
Complementary
Rated current - 10 AX
[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz
Electrical durability - 20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, $\cos phi = 0.3$

Opening distance ->3 mm

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0a€2.5 mmA² rigid cable

0a€|2.5 mmA² flexible cable

Material - Thermoplastic ABS-UV stabilised: mechanism rocker

PC (polycarbonate) GF10 FR: casing

CuZn37: terminals

PBT (polybutylene terephthalate) GF30: release button

Marking - Without marking

Surface finish - Matt

specific treatment - integrated within the material - Painted

Fixing mode - Clip-in

Width - 45 mm

Height - 45 mm

Depth - 34.25 mm

Embedding depth - 21.15 mm

Net weight - 0.0315 kg

Ambient air temperature for operation - -5a€|40 A°C

Ambient air temperature for storage - -5a€|50 A°C

Standards - IEC 60669-1

LV directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Oil

UV resistant

Acetone

Liquid soap

Window-cleaning fluid

Petrol

Alcohol

Bleach

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 3.9 cm

Package 1 Width - 4.5 cm

Package 1 Length - 4.5 cm

Package 1 Weight - 34.0 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 8.0 cm

Package 2 Width - 18.0 cm

Package 2 Length - 18.5 cm

Package 2 Weight - 427.0 g

Unit Type of Package 3 - S03

Number of Units in Package 3 - 80

Package 3 Height - 30.0 cm

Package 3 Width - 30.0 cm

Package 3 Length - 40.0 cm

Package 3 Weight - 3.868 kg

Pret: 59,92 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/buton-dublu-new-unica-1-pole-2-way-10ax-2-module-terminal-fara-suruburi-vopsit-ip4x-antracit-319007