



**SCHNEIDER BUTON DUBLU, NEW UNICA, 1-POLE 2-WAY, 10AX, 2 MODULE,  
TERMINAL FARA SURUBURI, VOPSIT, IP4X, ANTRACIT**

Schneider Electric New Unica switch NU321354 is a mechanism in color anthracite with 2 rockers. This is a double one-way switch. The fixing mode of this device is clip-in. Its rated current is 10AX. It is 45 mm in width, It is 45 mm in height, 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. This switch has screwless terminals connection terminals. Cu.Zn37, PBT (polybutylene terephthalate) GF30, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized It obtained AENOR, CE, EAC, NF certificate. Being environmentally friendly, this switch is a green premium product. It is mercury free.as well as heavy metal free, taking care of the environment and your health. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - 1-pole 2-way

Number of rocker - 2

Device application - Light control

Colour tint - Anthracite (RAL 7021)

Type of packing - Flow-pack

Complementary

Rated current - 10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles,  $\cos \phi = 0.6$

Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 2 modules  
Connections - terminals - Screwless terminals  
Cable cross section - 0a€¼2.5 mmA<sup>2</sup> rigid cable  
0a€¼2.5 mmA<sup>2</sup> flexible cable  
Material - Thermoplastic ABS-UV stabilised: mechanism rocker  
PC (polycarbonate) GF10 FR: casing  
CuZn37: terminals  
PBT (polybutylene terephthalate) GF30: release button  
Marking - Without marking  
Surface finish - Matt  
specific treatment - integrated within the material - Painted  
Fixing mode - Clip-in  
Width - 45 mm  
Height - 45 mm  
Depth - 34.25 mm  
Embedding depth - 21.15 mm  
Net weight - 0.0315 kg  
Ambient air temperature for operation - -5a€¼40 A°C  
Ambient air temperature for storage - -5a€¼50 A°C  
Standards - IEC 60669-1  
LV directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Oil  
UV resistant  
Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1  
Package 1 Height - 3.9 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 34.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.0 cm  
Package 2 Width - 18.0 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 427.0 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 80  
Package 3 Height - 30.0 cm  
Package 3 Width - 30.0 cm  
Package 3 Length - 40.0 cm  
Package 3 Weight - 3.868 kg  
Pret: 59,92 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/buton-dublu-new-unica-1-pole-2-way-10ax-2-module-terminal-fara-suruburi-vopsit-ip4x-antracit-319007>