



**SCHNEIDER INTERRUPTOR, NEW UNICA, MECANISM, 2-POLE 1-WAY, 20A, 2  
MODULE, SCREW TERMINALS, NETRATAT, IP4X, ALB**

Schneider Electric New Unica switch NU322518 is a mechanism in color white. This is a 2-pole 1-way switch. The fixing mode of this device is clip-in. Its rated current is 20A. It is 45 mm in width, 45 mm in height 29 mm in depth with an embedding depth of 15.5 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. This switch has screw terminals connection terminals. The switch is made of thermoplastic ABS-UV stabilized, making it resistant and durable. This switch is AENOR, CE, EAC, NF certified. This device is qualified as a green premium product, with minimal use of hazardous substances. It is mercury free. And heavy metal free, which takes care of the environment and your health as always. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - 2-pole 1-way

Number of rocker - 1

Device application - Light control

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 20 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles,  $\cos \phi = 0.6$

Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 2 modules  
Connections - terminals - Screw terminals  
Cable cross section - 0.4 mm<sup>2</sup> rigid cable  
0.4 mm<sup>2</sup> flexible cable  
Material - Thermoplastic ABS-UV stabilised: mechanism rocker  
Marking - Without marking  
Surface finish - Glossy  
specific treatment - integrated within the material - Untreated  
Fixing mode - Clip-in  
Width - 45 mm  
Height - 45 mm  
Depth - 29 mm  
Embedding depth - 15.5 mm  
Net weight - 0.0242 kg  
Ambient air temperature for operation - -5 to 40 A°C  
Ambient air temperature for storage - -5 to 50 A°C  
Standards - LV directive  
IEC 60669-1  
Product certifications - CE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Oil  
UV resistant  
Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 2.5 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 25.0 g  
Unit Type of Package 2 - S02  
Number of Units in Package 2 - 20

Package 2 Height - 15 cm  
Package 2 Width - 30 cm  
Package 2 Length - 40 cm  
Package 2 Weight - 980 g  
Pret: 42,94 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interruptor-new-unica-mecanism-2-pole-1-way-20a-2-module-screw-terminals-netratat-ip4x-alb-319008>