



SCHNEIDER INTRERUPATOR, NEW UNICA, MECANISM, 2-POLE 1-WAY, 16AX, 2 MODULE, SCREW TERMINALS, VOPSIT, IP4X, ALUMINIU

Schneider Electric New Unica switch NU326230 is a mechanism in color aluminium. This is a 2-pole 1-way switch. The fixing mode of this device is clip-in. Its rated current is 16AX. It is 45 mm in width, 45 mm in height 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screw terminals. The switch is made of Cu.Zn5 Ag, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, making it as resistant as possible. This switch is AENOR, CE, EAC, NF certified. As a green premium product, this device is environmentally friendly. This switch is mercury free and heavy metal free, which takes care of the environment and your health as always. Besides, there is a 0 - 1 marking on the surface. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - 2-pole 1-way

Number of rocker - 1

Device application - Light control

Colour tint - Aluminium

Type of packing - Flow-pack

Complementary

Rated current - 16 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, $\cos \phi = 0.6$

Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Opening distance - > 3 mm
Actuator - Rocker
Number of modules - 2 modules
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm² rigid cable
0.4 mm² flexible cable
Material - CuZn5 Ag: terminals
Thermoplastic ABS-UV stabilised: mechanism rocker
PC (polycarbonate) GF10 FR: casing
Marking - 0 - 1
Surface finish - Glossy
specific treatment - integrated within the material - Painted
Fixing mode - Clip-in
Width - 45 mm
Height - 45 mm
Depth - 37.75 mm
Embedding depth - 24.65 mm
Net weight - 0.0231 kg
Ambient air temperature for operation - -5 to 40 A°C
Ambient air temperature for storage - -5 to 50 A°C
Standards - IEC 60669-1
LV directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Oil
UV resistant
Acetone
Liquid soap
Window-cleaning fluid
Petrol
Alcohol
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1

Package 1 Height - 3.8 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 25 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8 cm
Package 2 Width - 18 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 335 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 80
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 3.122 kg
Pret: 39,03 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-mecanism-2-pole-1-way-16ax-2-module-screw-terminals-vopsit-ip4x-aluminiu-319012>