



**SCHNEIDER INTRERUPATOR, NEW UNICA, MECANISM, 1-POLE 1-WAY, 32A, 2
MODULE, SCREW TERMINALS, NETRATAT, IP4X, BEJ**

Schneider Electric New Unica switch NU323244S is a mechanism in color beige. This is a 1-pole 1-way switch with lamp. The device's fixing mode is clip-in. Its rated current is 32A. It is 45 mm in width, It is 45 mm in height, 32 mm in depth. The IP rating of this device is IP20. Its connection terminals are screw terminals. The switch is made of ABS (acrylonitrile butadiene-styrene), ASA + PC, making it resistant and durable. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism

Technology type - Electromechanical

Switch function - 1-pole 1-way

Number of rocker - 1

Device application - Light control

Colour tint - Beige (RAL 1013)

Type of packing - Flow-pack

Complementary

Rated current - 32 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 10000 cycles, $\cos \phi = 0.6$

Insulation resistance - $> 5 \text{ MOhm}$ at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, $\cos \phi = 0.3$

Condition of use - Indoor

Opening distance - > 3 mm
Actuator - Rocker
Number of modules - 2 modules
Pilot light - LED, colour: amber, current consumption: 1 mA, temperature rise: 15 A°C
Connections - terminals - Screw terminals
Cable cross section - 0a€¦6 mmA² flexible cable
0a€¦6 mmA² rigid cable
Material - ASA + PC: mechanism cover
ABS (acrylonitrile butadiene-styrene): mechanism cover
Surface finish - Glossy
specific treatment - integrated within the material - Untreated
Fixing mode - Clip-in
Width - 45 mm
Height - 45 mm
Depth - 41 mm
Embedding depth - 30 mm
Net weight - 0.039 kg
Ambient air temperature for operation - -5a€¦40 A°C
Ambient air temperature for storage - -5a€¦50 A°C
Standards - EN 60669-1
LV directive
EMC directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Oil
Liquid soap
Alcohol
Window-cleaning fluid
Petrol
Acetone
UV resistant
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.6 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm

Package 1 Weight - 47.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 5.5 cm
Package 2 Width - 30.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 567.0 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 100
Package 3 Height - 30.0 cm
Package 3 Width - 30.0 cm
Package 3 Length - 40.0 cm
Package 3 Weight - 6.111 kg
Pret: 98,27 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interruptor-new-unica-mecanism-1-pole-1-way-32a-2-module-screw-terminals-netratat-ip4x-bej-319123>