



SCHNEIDER BUTON JALUZELE, NEW UNICA, 10 A, 250 V, AC, 1 MODULE, BEJ

Schneider Electric New Unica switch NU310744SC is a mechanism in color beige. This is a roller blind push-button switch. Clip-in this rocker switch for the fixation. Its rated current is 10A. It is 22.4 mm in width, It is 45 mm in height, 33 mm in depth with an embedding depth of 21 mm. The IP rating of this device is IP20. This switch has screw terminals connection terminals. The switch is made of ASA + PC, making it resistant and durable. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Control

Product or component type - Shutter control

device presentation - Mechanism

Rated current - 10 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Clip-in

Colour tint - Beige (RAL 1013)

Complementary

device mounting - Flush

Number of modules - 1 module

Technology type - Electromechanical

Actuator - Rocker

Number of rocker - 2

Switch function - 1-pole 2-way

Switch application - Roller blind

Number of poles - 1

Contacts type and composition - 1 C/O

mechanical interlocking - Interlock between up/down

[I_u] rated interrupted current - 2.5 A for motor

Opening distance - > 3 mm

Pilot light - Without LED

Marking - UP

Down

Connections - terminals - Screw terminals

Cable cross section - 2.5 mm² flexible cable

1.5-2.5 mm² flexible cable

2.5 mm² rigid cable

1.5-2.5 mm² rigid cable

Minimum load breaking capacity - 200 operations 1.25 I_n and 1.1 U_n, cos phi = 0.3

Electrical durability - 10000 cycles, cos phi = 0.6

Insulation resistance - > 5 MΩ at 500 V

Dielectric strength - 2000 V

Material - ASA + PC: mechanism cover

ABS (acrylonitrile butadiene-styrene): mechanism cover

Standards - LV directive

EMC directive

EN 60669-1

Product certifications - ISI

CE

Ambient air temperature for operation - -5-40 °C

Ambient air temperature for storage - -5-40 °C

Embedding depth - 31.5 mm

Depth - 40.6 mm

Width - 22.5 mm

Height - 45 mm

Net weight - 0.035 kg

Environment

IK degree of protection - IK04

IP degree of protection - IP4X

Environmental characteristic - Petrol

Bleach

Oil

Window-cleaning fluid

Liquid soap

Alcohol

Acetone

UV resistant

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 4.05 cm

Package 1 Width - 2.25 cm

Package 1 Length - 4.5 cm

Package 1 Weight - 21 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 6.5 cm

Package 2 Width - 12 cm

Package 2 Length - 18.5 cm

Package 2 Weight - 278.3 g

Unit Type of Package 3 - S01

Number of Units in Package 3 - 40

Package 3 Height - 15 cm

Package 3 Width - 15 cm

Package 3 Length - 40 cm

Package 3 Weight - 1.313 kg

Pret: 43,99 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/buton-jaluzele-new-unica-10-a-250-v-ac-1-module-bej-319151>