



**SCHNEIDER BUTON JALUZELE, NEW UNICA, 10 A, 250 V, AC, 1 MODULE,**  
**ANTRACIT**

Schneider Electric New Unica switch NU310754SC is a mechanism in color anthracite. This is a roller blind push-button switch. Clip-in this rocker switch for the fixation. Its rated current is 10A. And 33 mm in depth with an embedding depth of 21 mm. The IP rating of this device is IP20. Its connection terminals are screw terminals. The switch is made of ASA + PC, making it resistant and durable. Besides, there is a UP, down marking on the surface. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Control

Product or component type - Shutter control

device presentation - Mechanism

Rated current - 10 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Fixing mode - Clip-in

Colour tint - Anthracite (RAL 7021)

Complementary

device mounting - Flush

Number of modules - 1 module

Technology type - Electromechanical

Actuator - Rocker

Number of rocker - 2

Switch function - 1-pole 2-way

Switch application - Roller blind

Number of poles - 1

Contacts type and composition - 1 C/O  
mechanical interlocking - Interlock between up/down  
[Iu] rated interrupted current - 2.5 A for motor  
Opening distance - > 3 mm  
Pilot light - Without LED  
Marking - Down  
UP  
Connections - terminals - Screw terminals  
Cable cross section - 2.5 mmA<sup>2</sup> flexible cable  
1.5a€2.5 mmA<sup>2</sup> flexible cable  
2.5 mmA<sup>2</sup> rigid cable  
1.5a€2.5 mmA<sup>2</sup> rigid cable  
Minimum load breaking capacity - 200 operations 1.25 I<sub>n</sub> and 1.1 U<sub>n</sub>, cos phi = 0.3  
Electrical durability - 40000 cycles, cos phi = 0.6  
10000 cycles, cos phi = 0.6  
Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Material - ASA + PC: mechanism cover  
ABS (acrylonitrile butadiene-styrene): mechanism cover  
Standards - EN 60669-1  
EMC directive  
LV directive  
Product certifications - ISI  
CE  
Ambient air temperature for operation - -5a€40 A°C  
Ambient air temperature for storage - -5a€40 A°C  
Embedding depth - 31.5 mm  
Depth - 40.6 mm  
Width - 22.5 mm  
Height - 45 mm  
Net weight - 0.035 kg  
Environment  
IK degree of protection - IK04  
IP degree of protection - IP4X  
Environmental characteristic - Oil  
Liquid soap  
UV resistant  
Bleach  
Petrol  
Acetone  
Window-cleaning fluid  
Alcohol  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 4.05 cm  
Package 1 Width - 2.25 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 21 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 6.5 cm  
Package 2 Width - 12 cm  
Package 2 Length - 18.5 cm

Package 2 Weight - 278.3 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 160  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 4.894 kg  
Pret: 55,63 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/buton-jaluzele-new-unica-10-a-250-v-ac-1-module-antracit-319152>