



SCHNEIDER INTERRUPATOR, NEW UNICA, 2 MODULE, IP44, ALB

Schneider Electric New Unica switch NU528218 is a in color white. This is an IP44 switch with 2 modules. With IP44 level reached, the device has better performance against solid particle and liquid. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - 1-pole 2-way

Number of rocker - 1

Device application - Light control

Provided equipment - Membrane

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, $\cos \phi = 0.6$

Insulation resistance - $> 5 \text{ MOhm}$ at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, $\cos \phi = 0.3$

Condition of use - Indoor

Opening distance - $> 3 \text{ mm}$

Actuator - Rocker

Connections - terminals - Screwless terminals
Cable cross section - 0a€|2.5 mmA² rigid cable
0a€|2.5 mmA² flexible cable
Material - ABS (acrylonitrile butadiene-styrene): mechanism cover
Marking - IP44
Surface finish - Glossy
specific treatment - integrated within the material - Untreated
Fixing mode - Screws or claws
Width - 74.5 mm
Height - 74.5 mm
Depth - 34.25 mm
Embedding depth - 21.15 mm
Net weight - 0.071 kg
Ambient air temperature for operation - -5a€|40 A°C
Ambient air temperature for storage - -5a€|50 A°C
Standards - EN 60669-1
LV directive
EMC directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Alcohol
Window-cleaning fluid
Acetone
Petrol
UV resistant
Oil
Bleach
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.5 cm
Package 1 Width - 7.5 cm
Package 1 Length - 7.5 cm
Package 1 Weight - 66.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8.2 cm

Package 2 Width - 19.7 cm
Package 2 Length - 22.6 cm
Package 2 Weight - 765.0 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 120
Package 3 Height - 30.0 cm
Package 3 Width - 40.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 9.883 kg
Pret: 51,40 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-2-module-ip44-alb-319161>