



### **SCHNEIDER INTRERUPATOR, NEW UNICA, 2 MODULE, IP44, ALUMINIU**

Schneider Electric New Unica switch NU528230 is a in color aluminium. This is an IP44 switch with 2 modules. With IP44 level reached, the device has better performance against solid particle and liquid. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - 1-pole 2-way

Number of rocker - 1

Device application - Light control

Provided equipment - Membrane

Colour tint - Aluminium

Type of packing - Flow-pack

Complementary

Rated current - 10 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles,  $\cos \phi = 0.6$

Insulation resistance -  $> 5 \text{ MOhm}$  at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un,  $\cos \phi = 0.3$

Condition of use - Indoor

Opening distance -  $> 3 \text{ mm}$

Actuator - Rocker

Number of modules - 2 modules  
Connections - terminals - Screwless terminals  
Cable cross section - 0a€2.5 mmA<sup>2</sup> rigid cable  
0a€2.5 mmA<sup>2</sup> flexible cable  
Material - ABS (acrylonitrile butadiene-styrene): mechanism cover  
Marking - IP44  
Surface finish - Glossy  
specific treatment - integrated within the material - Painted  
Fixing mode - Screws or claws  
Width - 74.5 mm  
Height - 74.5 mm  
Depth - 34.25 mm  
Embedding depth - 21.15 mm  
Net weight - 0.071 kg  
Ambient air temperature for operation - -5a€40 A°C  
Ambient air temperature for storage - -5a€50 A°C  
Standards - EN 60669-1  
LV directive  
EMC directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Alcohol  
Window-cleaning fluid  
Acetone  
Petrol  
UV resistant  
Oil  
Bleach  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 3.5 cm  
Package 1 Width - 7.5 cm  
Package 1 Length - 7.5 cm  
Package 1 Weight - 66.0 g  
Unit Type of Package 2 - S02  
Number of Units in Package 2 - 10

Package 2 Height - 15.0 cm  
Package 2 Width - 30.0 cm  
Package 2 Length - 40.0 cm  
Package 2 Weight - 1080.0 g  
Unit Type of Package 3 - P06  
Number of Units in Package 3 - 160  
Package 3 Height - 77.0 cm  
Package 3 Width - 60.0 cm  
Package 3 Length - 80.0 cm  
Package 3 Weight - 25.78 kg  
Pret: 59,12 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interruptor-new-unica-2-module-ip44-aluminiu-319162>