



### **SCHNEIDER VARIATOR, NEW UNICA, ROTARY PUSH TYPE, ALB**

Schneider Electric New Unica dimmer NU351418 is a mechanism in color white with 2 modules. 230V is the rated operational voltage. And the associated fuse rating is 16. And the control type of this dimmer is local control, remote control by auxiliary push-button. Its protection type is automatic overload protection, overheating protection, short-circuit protection, taking care of your safety as much as possible. Its matching mounting box can be recessed into the surface of the wall with flush type. The connection terminals of this dimmer are screw terminal. What's more, its directives are 2014/30/EU - electromagnetic compatibility, 2014/35/EU - low voltage directive. It is 45 mm in width, 45 mm in height, 47 mm in depth, and with an embedding depth of 29 mm. And the product weighs 0.129 kg. Besides, the IP rating of this device is IP20, IP21. It obtained CE, EAC, FIMKO, NEMKO, NF, SEMKO, VDE certificate as well. What's more, it well satisfied the standard of EN 300-328, EN 301-489-17, EN 60669-2-1, EN 60730-2-7. And it is mercury free. As a green premium product, this device is environmentally friendly as well. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Product brand - Schneider Electric

Range - New Unica

Type number - NH3514

Product or component type - Dimmer

Complementary

device presentation - Mechanism

Device application - Light control

Dimmer type - Universal

Dimmer control - Rotary push type

Load type - Incandescent lamp: 5...200 W at 230 V AC

Halogen lamp: 5...150 W at 230 V AC

LED lamp: 5...100 VA at 230 V AC (RC LED mode)

LED lamp: 5...20 VA at 230 V AC (RL LED mode)

LV halogen lamps: 5...150 VA at 12 V AC (electronic transformer)  
LV halogen lamps: 5...150 VA at 12 V AC (wound transformer)  
Function available - With memory function  
[Ue] rated operational voltage - 230 V AC 50 Hz  
Associated fuse rating - 16 A  
Protection type - Automatic overload protection  
Overheating protection  
Short-circuit protection  
colour - White (RAL 9003)  
Surface finish - Glossy  
Number of modules - 2 modules  
Number of outputs - 1  
Control type - Local control dimming up/down control  
Local control automatic load detection  
Remote control by auxiliary push-button  
Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m  
Provided equipment - User manual  
Connections - terminals - Screw terminal  
Number of loop terminals - 2  
Clamping connection capacity - 1.5...2.5 mmA<sup>2</sup> for solid cable(s)  
1.5...2.5 mmA<sup>2</sup> for solid stranded cable(s)  
Shape of screw head - Pozidriv No 1 and combi  
Tightening torque - 0.5 N.m  
Material - PC (polycarbonate) GF10 FR: casing  
Metal: terminals  
Thermoplastic ABS-UV stabilised: central plate  
device mounting - Flush  
Fixing mode - By screws  
Type of installation - Indoor installation  
Quantity per set - 1 carton  
Embedding depth - 29 mm  
Depth - 47 mm  
Width - 45 mm  
Height - 45 mm  
Net weight - 0.129 kg  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation - 5a€140 A°C  
Ambient air temperature for storage - 5a€140 A°C  
IP degree of protection - IP20  
IP21 with marking on visual parts  
IK degree of protection - IK04  
Environmental characteristic - UV resistant  
Oil  
Window-cleaning fluid

Bleach  
Acetone  
Liquid soap  
Alcohol  
Petrol  
Standards - EN 60730-2-7  
EN 301-489-17  
EN 60669-2-1  
EN 300-328  
Directives - 2014/30/EU - electromagnetic compatibility  
2014/35/EU - low voltage directive  
Product certifications - NF  
NEMKO  
EAC  
VDE  
SEMKO  
FIMKO  
CE  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 7.8 cm  
Package 1 Width - 9.5 cm  
Package 1 Length - 9.5 cm  
Package 1 Weight - 111 g  
Unit Type of Package 2 - S02  
Number of Units in Package 2 - 9  
Package 2 Height - 15 cm  
Package 2 Width - 30 cm  
Package 2 Length - 40 cm  
Package 2 Weight - 1.467 kg  
Unit Type of Package 3 - P06  
Number of Units in Package 3 - 144  
Package 3 Height - 77 cm  
Package 3 Width - 80 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 31.972 kg  
Pret: 589,95 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/variator-new-unica-rotary-push-type-alb-319198>