



### **SCHNEIDER NEW UNICA - LIGHT MODULE - 230 V DC - 2 MODULE**

Schneider Electric New Unica light module NU3772 is a mechanism in color. The connection terminals of this light module are screw terminals. It is 45 mm in width, 45 mm in height, 31 mm in depth, with an embedding depth of 21 mm, and the product weighs 0.035 kg. With 2 modules. Its fixing mode is clip-in. In addition, the rated operational voltage of this device is 230V. Besides, it is halogen free, which is good for your health. And it is mercury free and heavy metal free, which takes care of the environment and your health as always. Being made of PC (polycarbonate) GF10 FR material, this light module is quite reliable and resistant. The maximum input power of this light module is 0.2, 1 W. Besides, it reaches IK03 protection level, which can help protect against impact. What's more, it satisfies the standard of CE, EN 62094-1. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This light module is SVHC (substances of very high concern) free too. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install, providing solutions for all customers' requirements.

Range - New Unica

Product or component type - Light module

device presentation - Mechanism

[Ue] rated operational voltage - 230 V AC at 50...60 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White

Complementary

Input power - 1 W

0.2 W

Light block colour - White

Bulb type - LED

Connections - terminals - Screw terminals

Clamping connection capacity -  $\leq 2 \times 2.5 \text{ mm}^2$  for flexible cable(s)

$\leq 2 \times 2.5 \text{ mm}^2$  for rigid cable(s)

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Standards - EN 62094-1

CE

Directives - 2014/35/EU - low voltage directive

Ambient air temperature for operation -  $-5^{\circ}\text{C}$  to  $+45^{\circ}\text{C}$

Ambient air temperature for storage -  $-5^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$

Embedding depth - 21 mm

Depth - 31 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.035 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK03

IP degree of protection - IP2xC

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 6.500 cm

Package 1 Width - 8.000 cm

Package 1 Length - 8.800 cm

Package 1 Weight - 71.000 g

Unit Type of Package 2 - S02

Number of Units in Package 2 - 27

Package 2 Height - 15.000 cm

Package 2 Width - 30.000 cm

Package 2 Length - 40.000 cm

Package 2 Weight - 2.176 kg

Pret: 105,93 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-light-module-230-v-dc-2-module-319231>