



### **SCHNEIDER NEW UNICA - LIGHT MODULE - 12...24 V AC - 2 MODULE - ALB**

Schneider Electric New Unica light module NU3773 is a mechanism in color. Its connection terminals are screw terminals. It is 45 mm in width, 45 mm in height, 31 mm in depth, with an embedding depth of 21 mm, and the product weighs 0.035 kg. With 2 modules. The fixing mode of this device is clip-in. 12...24V is the rated operational voltage. Besides it is halogen free, which is good for your health. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time. The light module is made of PC (polycarbonate) GF10 FR, making it as resistant as possible. The maximum input power of this light module is 0.7 W. Besides, it reaches IK03 protection level, which can help protect against impact. What's more, its directives are 2014/35/EU - low voltage directive. What's more, it well satisfied the standard of CE, EN 62094-1. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This light module is SVHC (substances of very high concern) free too. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Light module

device presentation - Mechanism

[Ue] rated operational voltage - 12...24 V DC

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White

Complementary

Input power - 0.7 W

Light block colour - White

Bulb type - LED

Connections - terminals - Screw terminals

Clamping connection capacity -  $\leq 2 \times 2.5 \text{ mm}^2$  for flexible cable(s)

$\leq 2 \times 2.5 \text{ mm}^2$  for rigid cable(s)

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Standards - EN 62094-1

CE

Directives - 2014/35/EU - low voltage directive

Ambient air temperature for operation -  $-5 \text{ a } 45 \text{ A}^\circ\text{C}$

Ambient air temperature for storage -  $-5 \text{ a } 50 \text{ A}^\circ\text{C}$

Embedding depth - 21 mm

Depth - 31 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.035 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK03

IP degree of protection - IP2xC

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 6.3 cm

Package 1 Width - 8.0 cm

Package 1 Length - 8.5 cm

Package 1 Weight - 61.0 g

Unit Type of Package 2 - S02

Number of Units in Package 2 - 27

Package 2 Height - 15 cm

Package 2 Width - 30 cm

Package 2 Length - 40 cm

Package 2 Weight - 1.941 kg

Package 3 Height - 77 cm

Pret: 213,94 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-light-module-12-24-v-ac-2-module-alb-319232>