



SCHNEIDER NEW UNICA - EMERGENCY LIGHT - 230 V AC - 2 MODULE

Schneider Electric New Unica emergency light NU3776 is a complete mechanism in color white with 2 modules. Its connection terminals are screw terminals. This emergency lighting provides 45 lux per 25 cm and has an integrated battery. Being made of PC (polycarbonate) GF10 FR material, this emergency light is quite reliable and resistant. The rated operational voltage of this device is 230V. It is 45 mm in width, 45 mm in height, 43 mm in depth, with an embedding depth of 32 mm. And the product weighs 0.085 kg. Besides it is halogen free halogen free, which is good for your health. The fixing mode of this device is clip-in. It well satisfied the standard of CE, EN 60598-2-22. What's more, its directives are 2014/35/EU - low voltage directive. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This emergency light is SVHC (substances of very high concern) free too. Besides, it reaches IK03 and IP2xC protection levels, which can help protect against impact. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time.

Main

Range - New Unica

Product or component type - Emergency light

device presentation - Mechanism

[Ue] rated operational voltage - 230 V AC +/- 10 % at 50 Hz

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White

Complementary

Condition of use - Battery and bulb cannot be replaced

Light block colour - Green

Bulb type - LED

Bulb lifespan - 400 h

Illuminance - 25 cm: 45 lux

Connections - terminals - Screw terminals

Clamping connection capacity - $\leq 2 \times 2.5 \text{ mm}^2$ for flexible cable(s)

$\leq 2 \times 2.5 \text{ mm}^2$ for rigid cable(s)

Charging time - 24 h

Electrical durability - 500 cycles

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Standards - EN 60598-2-22

CE

Directives - 2014/35/EU - low voltage directive

Ambient air temperature for operation - $-5 \text{ a } 45 \text{ A}^\circ\text{C}$

Ambient air temperature for storage - $-5 \text{ a } 50 \text{ A}^\circ\text{C}$

Embedding depth - 32 mm

Depth - 43 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.085 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK03

IP degree of protection - IP2xC

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 6.4 cm

Package 1 Width - 8.0 cm

Package 1 Length - 8.6 cm

Package 1 Weight - 80.0 g

Unit Type of Package 2 - S02

Number of Units in Package 2 - 27

Package 2 Height - 15.0 cm

Package 2 Width - 30.0 cm

Package 2 Length - 40.0 cm

Package 2 Weight - 2.464 kg

Pret: 561,55 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/new-unica-emergency-light-230-v-ac-2-module-319235>