

SCHNEIDER NEW UNICA - EMERGENCY LIGHT - 230 V AC - 2 MODULE

Schneider Electric New Unica emergency light NU3776 is a complete mechanism in color white with 2 modules. Its connection terminals are screw terminals. This emergency lighting provides 45 lux per 25 cm and has an integrated battery. Being made of PC (polycarbonate) GF10 FR material, this emergency light is quite reliable and resistant. The rated operational voltage of this device is 230V. It is 45 mm in width, 45 mm in height, 43 mm in depth, with an embedding depth of 32 mm. And the product weighs 0.085 kg. Besides it is halogen free halogen free, which is good for your health. The fixing mode of this device is clip-in. It well satisfied the standard of CE, EN 60598-2-22. What's more, its directives are 2014/35/EU - low voltage directive. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This emergency light is SVHC (substances of very high concern) free too. Besides, it reaches IK03 and IP2xC protection levels, which can help protect against impact. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time.Main
Range - New Unica
Product or component type - Emergency light
device presentation - Mechanism
[Ue] rated operational voltage - 230 V AC +/- 10 % at 50 Hz
Number of modules - 2 modules
Fixing mode - Clip-in
Colour tint - White
Complementary
Condition of use - Battery and bulb cannot be replaced
Light block colour - Green
Bulb type - LED
Bulb lifespan - 400 h
Illuminance - 25 cm: 45 lux
Connections - terminals - Screw terminals
Clamping connection capacity - <= 2 x 2.5 mmA² for flexible cable(s)

<= 2 x 2.5 mmA² for rigid cable(s)
Charging time - 24 h
Electrical durability - 500 cycles
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
Standards - EN 60598-2-22
CE
Directives - 2014/35/EU - low voltage directive
Ambient air temperature for operation - 5a€¦45 A°C
Ambient air temperature for storage - -5a€¦50 A°C
Embedding depth - 32 mm
Depth - 43 mm
Width - 45 mm
Height - 45 mm
Net weight - 0.085 kg
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IK degree of protection - IK03
IP degree of protection - IP2xC
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 6.4 cm
Package 1 Width - 8.0 cm
Package 1 Length - 8.6 cm
Package 1 Weight - 80.0 g
Unit Type of Package 2 - S02
Number of Units in Package 2 - 27
Package 2 Height - 15.0 cm
Package 2 Width - 30.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 2.464 kg
Pret: 565,85 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/new-unica-emergency-light-230-v-ac-2-module-319235