



## **SCHNEIDER NEW UNICA - STATIE DE LUCRU - INCASTRAT - 3 X 4 MODULE - ALB**

Schneider Electric New Unica workstation NU173418 is in color white. It is 230 mm in width, 165 mm in height, 62 mm in depth. And the product weighs 0.401 kg. With 3 x 4 modules. The device's fixing mode is claws, embedment. Its matching mounting box can be recessed into the surface of the wall with flush type. The workstation is made of ABS (acrylonitrile butadiene-styrene), PC, making it as resistant as possible. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This workstation is SVHC (substances of very high concern) free too. This device is (compatible with) Unica. Besides it is halogen free halogen free, which is good for your health. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Workstation

Number of modules - 3 x 4 modules

Fixing mode - Embedment

Claws

Colour tint - White (RAL 9003)

Complementary

Provided equipment - Fixing frame

Cover frame

device mounting - Flush

Cable entry - 6 knock-outs 20 mm for diameter

6 knock-outs 25 mm for diameter

2 bottom cable entries 45 x 25 mm for size 20 mm for diameter

4 bottom cable entries 50 x 35 mm for size 25 mm for diameter

Fire resistance - 850 A°C, extinction time <30 s

Material - ABS (acrylonitrile butadiene-styrene): separator

PC: box  
ABS (acrylonitrile butadiene-styrene): cover frame  
Depth - 62 mm  
Width - 230 mm  
Height - 165 mm  
Net weight - 0.401 kg  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IK degree of protection - IK04  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 7.9 cm  
Package 1 Width - 17.9 cm  
Package 1 Length - 25.0 cm  
Package 1 Weight - 520.0 g  
Unit Type of Package 2 - S04  
Number of Units in Package 2 - 14  
Package 2 Height - 30.0 cm  
Package 2 Width - 40.0 cm  
Package 2 Length - 60.0 cm  
Package 2 Weight - 7.794 kg  
Unit Type of Package 3 - P06  
Number of Units in Package 3 - 56  
Package 3 Height - 77.0 cm  
Package 3 Width - 80.0 cm  
Package 3 Length - 60.0 cm  
Package 3 Weight - 40.66 kg  
Pret: 133,62 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-statie-de-lucru-incastrat-3-x-4-module-alb-319728>