



BTICINO L.NOW - LAMPA DE LECTURA+DEV. 230 V C.A.

Descoper? L.NOW - Lamp? de lectur?+dev. 230 V c.a. din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul KW4362. Acesta ofer? caracteristici excelente: Suitable for wall mounting Yes

Suitable for suspended mounting No

Suitable for ceiling mounting No

Suitable for built-in mounting Yes

Suitable for surface mounting Yes

Suitable for light line configuration No

Suitable for workplace according to EN 12464-1 No

Lamp type LED not exchangeable

With light source Yes

Suitable for number of light sources 1

Lamp holder Other

Housing material Plastic

Surface protection housing Untreated

Housing colour Black

Material cover Plastic, opal

Type of grid White

Voltage type AC

Nominal voltage 230-250 V

Nominal current 15-25 mA

Type of control gear LED operating device voltage-controlled

With control gear No

Exchangeable control gear No

Dimming 0-10 V No

Dimming 1-10 V No

Dimming DALI-2 No

Dimming DALI No

Dimming DMX No
Dimming DSI No
Dimming potentiometer (integrated) No
Dimming LineSwitch No
Dimming manufacturer's proprietary system No
Dimming mains voltage modulation No
Dimming phase cut-off No
Dimming phase cut-on No
Dimming programmable Yes
Dimming RF No
Dimming Sine Wave Reduction No
Dimming Touch and Dim Yes
Dimming Zigbee No
Dimming with push-button Yes
No dim function No
Light distributor Diffuser lens/optic/panel
Light sharing Symmetric/asymmetric
Beam angle Open beam/diffuse
Light outlet Direct
Degree of protection (IP) IP40
Degree of impact strength (IK) IK04
Protection class None
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 No
Rated ambient temperature according to IEC 62722-2-1 -5-35 °C
Suitable for emergency lighting No
Emergency power supply integrated No
With movement sensor No
With light sensor No
Covering of the luminaire with thermally insulating material possible No
With air slots Yes
Filament test according to IEC 60695-2-11 None
Suitable for lamp power 0.1-0.2 W
Max. system power 0.3 W
Rated luminous flux according to IEC 62722-2-1 246 lm
Colour of light White
Colour temperature 4000-5500 K
Colour rendering index CRI 80-89
Width 22 mm
Height/depth 375 mm
Length 86 mm
Built-in width 22 mm
Built-in height/depth 86 mm
Type of wiring Ending
Number of poles 2
Conductor cross section 1.5 mm²
Connection type Screwed terminal
Operation by Bluetooth No
Compatible with Apple HomeKit No
Compatible with Google Assistant No
Compatible with Amazon Alexa No
IFTTT support available No
Operating / setting temperature -5-35 °C
Storage temperature -10-70 °C
Frequency 50-60 Hz

Standby consumption 136 mA

Mandatory neutral No

RAL-number 9003

Halogen free Yes

Antimicrobial treatment No

Terminals capacity 1-1.5 mm²

Cable nature for connection Flexible or rigid

With socket outlet No

Fitted with rainproof plate protection No

With complementary luminous signal No

Supplied remote control No

Maximum Input cable diameter 2.5 mm

Vertical fixing center distance 9-9.2 mm

Horizontal fixing center distance 4-4.2 mm

Cable support Screw cable clamp

Auto switch No

Control mode Wired

Addressable No

Connected object No. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara.

Pret: 566,07 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/l-now-lampa-de-lectura-dev-230-v-c-a>