



BTICINO MATIX - LAMPA MONTAJ INCASTRAT CU LEDURI 1 MOD

Descoper? matix - Lamp? montaj incastat cu leduri 1 mod din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul A5781. Acesta ofer? caracteristici excelente: Suitable for wall mounting Yes

Suitable for suspended mounting No

Suitable for ceiling mounting No

Suitable for built-in mounting Yes

Suitable for surface mounting No

Suitable for light line configuration No

Suitable for workplace according to EN 12464-1 No

Lamp type LED not exchangeable

With light source Yes

Lamp holder Other

Housing material Plastic

Housing colour White

Material cover Plastic, opal

Type of grid White

Voltage type AC

Nominal voltage 230-250 V

Nominal current 15-25 mA

Type of control gear LED operating device voltage-controlled

With control gear No

Dimming 0-10 V No

Dimming 1-10 V No

Dimming DALI No

Dimming DMX No

Dimming DSI No

Dimming potentiometer (integrated) No

Dimming LineSwitch No

Dimming manufacturer's proprietary system No
Dimming mains voltage modulation No
Dimming phase cut-off No
Dimming phase cut-on No
Dimming programmable No
Dimming RF No
Dimming Sine Wave Reduction No
Dimming Touch and Dim No
Dimming Zigbee No
Dimming with push-button No
No dim function Yes
Light sharing Symmetric
Beam angle Extreme wide beam $>80^{\circ}$
Light outlet Direct
Degree of protection (IP) IP41
Protection class None
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 No
Rated ambient temperature according to IEC 62722-2-1 -5-49 °C
Suitable for emergency lighting Yes
With movement sensor No
With light sensor Yes
Covering of the luminaire with thermally insulating material possible No
With air slots Yes
Suitable for lamp power 0.1-0.1 W
Max. system power 0 W
Rated luminous flux according to IEC 62722-2-1 249 lm
Colour of light White
Colour temperature 4000-5500 K
Colour rendering index CRI 80-89
Width 23.4 mm
Height/depth 49.2 mm
Length 51 mm
Built-in length 47 mm
Built-in width 23.4 mm
Built-in height/depth 49.2 mm
Operating / setting temperature -5-49 °C
Storage temperature -10-69 °C
Frequency 50-50 Hz
Standby consumption 139 mA
Mandatory neutral No
Halogen free Yes
Antimicrobial treatment No
Terminals capacity 1.5-2.5 mm²
Cable nature for connection Flexible
With socket outlet No
Fitted with rainproof plate protection No
With complementary luminous signal No
Supplied remote control No
Maximum Input cable diameter 2.5 mm
Vertical fixing center distance 4.5-4.5 mm
Cable support Screw cable clamp
Control mode Wired
Connected object No. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara?
Pret: 447,71 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/matix-lampa-montaj-incastrat-cu-leduri-1-mod>