

BTICINO MATIX - DISJUNCTOR MAGNETO-TERMIC DIFEREN TIAL 10A 10MA

Descoper? matix - disjunctor magneto-termic diferen?ial 10A 10mA din categoria Prize, Intrerupatoare & Doze - Doza modulara, un produs cu codul AM5250S. Acesta ofer? caracteristici excelente: Number of poles (total) 2
Number of protected poles 1
Rated voltage 230 V
Rated current 10 A
Rated fault current 0.01 A
Leakage current type Other
Current limiting class 1
Rated short-circuit breaking capacity according to EN 61009 3 kA
Rated short-circuit breaking capacity according to IEC 60947-2 3 kA
Rated short-circuit breaking capacity Icn according to EN 61009-1 3 kA
Frequency 50/60 Hz
Release characteristic C
Concurrently switching neutral conductor No
Ambient temperature during operating -5-50 °C
Width in number of modular spacings 47.1
Built-in depth 47 mm
Degree of protection (IP) IP20
Connectable conductor cross section solid-core 2.5-2.5 mm²
Width 47.1 mm
Height 47 mm
Depth 47 mm
Degree of impact strength (IK) Not applicable
Storage temperature -10-70 °C
Connection type Screwed terminal. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.
Pret: 551,95 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/matix-disjunctor-magneto-termic-diferen-tial-10a-10ma