



1MODUL/POL-FIR TRAD.

Rated fault current adjustable No

Max. delay time 0 ms

Delay adjustable No

Number of poles 4

Leakage current type F

Frequency 50 Hz

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 4 kV

Connectable conductor cross section solid-core 1.5-35 mm²

Connectable conductor cross section multi-wired 1.5-25 mm²

Anti-nuisance tripping version Yes

With interlocking device Yes

Degree of protection (IP) IP20

Pollution degree 2

Ambient temperature during operating -25-70 °C

Width 124.6 mm

Height 96 mm

Depth 78 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Voltage type AC

Terminal marking indication Yes

Colour Green/yellow

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Cable

Mounting method DIN rail

Connected object No

Application store for download Not applicable. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara.

Pret: 358,83 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/bloc-dif-adaptat-dx3-surub-4p-400v-63a-tip-hpi-300ma-disj-1modul-pol-fir-trad>