



LEGRAND* DISJUNCTOR DX3 1P C0,5 10 KA

Descoper? Disjuncteur DX3 1P C0,5 10 kA din categoria Sigurante automate - Bipolare, un produs cu codul 409106. Acesta ofer? caracteristici excelente: Built-in depth 44 mm

Release characteristic C

Number of poles (total) 1

Number of protected poles 1

Rated current 0.5 A

Rated voltage 230 V

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 4 kV

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V 10 kA

Voltage type AC

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V 16 kA

Frequency 50-60 Hz

Current limiting class 3

Flush-mounted installation Yes

Concurrently switching neutral conductor No

Pollution degree 2

Additional equipment possible Yes

Width in number of modular spacings 1

Degree of protection (IP) IP20

Ambient temperature during operating -25-70 °C

Connectable conductor cross section multi-wired 1.5-25 mm²

Connectable conductor cross section solid-core 1.5-35 mm²

Explosion-proof No

Width 17.8 mm

Height 94.8 mm

Depth 77.8 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Electric supplying direction By the top or bottom

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal

Label space/information surface Yes

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 90,86 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjuntor-dx3-1p-c0-5-10-ka>