



### **LEGRAND\* DISJUNCTOR DX<sup>3</sup> MA-3P-400V~2,5A-25KA-MAGNETIC SIMPLU - 3M**

Descoper? Disjuncteur DX<sup>3</sup> MA-3P-400V~2,5A-25kA-magnetic simplu - 3M din categoria Sigurante automate - Tripolare, un produs cu codul 409877. Acesta ofer? caracteristici excelente: Built-in depth 44 mm  
Release characteristic MA

Number of poles (total) 3

Number of protected poles 3

Rated current 2.5 A

Rated voltage 400 V

Rated insulation voltage  $U_i$  500 V

Rated impulse withstand voltage  $U_{imp}$  4 kV

Voltage type AC

Rated short-circuit breaking capacity  $I_{cu}$  according to IEC 60947-2 at 230 V 50 kA

Rated short-circuit breaking capacity  $I_{cu}$  according to IEC 60947-2 at 400 V 25 kA

Frequency 50-60 Hz

Flush-mounted installation Yes

Concurrently switching neutral conductor No

Pollution degree 3

Additional equipment possible Yes

Width in number of modular spacings 3

Degree of protection (IP) IP20

Ambient temperature during operating -25-70 °C

Connectable conductor cross section multi-wired 1.5-25 mm<sup>2</sup>

Connectable conductor cross section solid-core 1.5-35 mm<sup>2</sup>

Explosion-proof No

Width 53.1 mm

Height 94.8 mm

Depth 77.8 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Nominal voltage 360-440 V

Electric supplying direction By the top or bottom

Terminal marking indication No

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Busbar and cable

Label space/information surface Yes

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 239,24 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-dx3-ma-3p-400v-2-5a-25ka-magnetic-simplu-3m>