



LEGRAND DISJUNCTOR DX³ MA-4P-400V~-40A-25KA-MAGNETIC SIMPLU - 6M

Descoper? Disjuncteur DX³ MA-4P-400V~-40A-25kA-magnetic simplu - 6M din categoria Sigurante automate - Tetrapolare, un produs cu codul 409894. Acesta ofer? caracteristici excelente: Built-in depth 47 mm

Release characteristic MA

Number of poles (total) 4

Number of protected poles 4

Rated current 40 A

Rated voltage 400 V

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 6 kV

Voltage type AC

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V 50 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V 25 kA

Frequency 50-60 Hz

Flush-mounted installation Yes

Concurrently switching neutral conductor Yes

Pollution degree 3

Additional equipment possible Yes

Width in number of modular spacings 6

Degree of protection (IP) IP20

Ambient temperature during operating -25-70 °C

Connectable conductor cross section multi-wired 1.5-35 mm²

Connectable conductor cross section solid-core 1.5-50 mm²

Explosion-proof No

Width 106.8 mm

Height 127.5 mm

Depth 79.2 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Nominal voltage 360-440 V

Electric supplying direction By the top or bottom

Terminal marking indication No

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Cable

Label space/information surface Yes

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 679,62 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/disjunctori-dx3-ma-4p-400v-40a-25ka-magnetic-simplu-6m>