



LEGRAND* DISJUNCTOR TX3 4P B3 10 KA

Descoper? Disjuncteur TX3 4P B3 10 kA din categoria Sigurante automate - Tetrapolare, un produs cu codul 404149. Acesta ofer? caracteristici excelente: Built-in depth 44 mm

Release characteristic B

Number of poles (total) 4

Number of protected poles 4

Rated current 3 A

Rated voltage 400 V

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 4 kV

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V 16 kA

Voltage type AC

Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V 10 kA

Frequency 50-60 Hz

Current limiting class 3

Flush-mounted installation Yes

Concurrently switching neutral conductor Yes

Pollution degree 2

Additional equipment possible Yes

Width in number of modular spacings 4

Degree of protection (IP) IP20

Explosion-proof No

Width 70.8 mm

Height 88 mm

Depth 77.8 mm

Degree of impact strength (IK) IK02

Storage temperature -40-70 °C

Nominal voltage 240-415 V

Electric supplying direction By the top or bottom

Terminal marking indication No

Colour Grey

RAL-number 7035

Halogen free Yes

Connection type Screwed terminal , Busbar and cable

Label space/information surface Yes

Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.

Pret: 181,84 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/disjunctor-tx3-4p-b3-10-ka>