

LEGRAND DISJUNCTOR DX³-2P-230/400V~-32A-25KA-CURBA B - 2M

Descoper? Disjunctor DX³-2P-230/400V~-32A-25kA-curb? B - 2M din categoria Sigurante automate - Bipolare, un produs cu codul 409719. Acesta ofer? caracteristici excelente: Built-in depth 44 mm
Release characteristic B
Number of poles (total) 2
Number of protected poles 2
Rated current 32 A
Rated voltage 400 V
Rated insulation voltage Ui 500 V
Rated impulse withstand voltage Uimp 4 kV
Voltage type AC
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V 50 kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V 25 kA
Frequency 50-60 Hz
Flush-mounted installation Yes
Concurrently switching neutral conductor No
Pollution degree 3
Additional equipment possible Yes
Width in number of modular spacings 2
Degree of protection (IP) IP20
Ambient temperature during operating -25-70 °C
Connectable conductor cross section multi-wired 1.5-25 mm²
Connectable conductor cross section solid-core 1.5-35 mm²
Explosion-proof No
Width 35.4 mm
Height 94.8 mm
Depth 77.8 mm
Degree of impact strength (IK) IK02

Storage temperature -40-70 °C
Nominal voltage 360-440 V
Electric supplying direction By the top or bottom
Terminal marking indication No
Colour Grey
RAL-number 7035
Halogen free Yes
Connection type Screwed terminal , Busbar and cable
Label space/information surface Yes
Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.
Pret: 170,25 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/disjunctor-dx3-2p-230-400v-32a-25ka-curba-b-2m