

LEGRAND* DISJUNCTOR DX³-4P-400V~-80A-25KA-CURBA B - 6M

Descoper? Disjunctor DX³-4P-400V~-80A-25kA-curb? B - 6M din categoria Sigurante automate - Tetrapolare, un produs cu codul 409749. Acesta ofer? caracteristici excelente: Built-in depth 47 mm
Release characteristic B
Number of poles (total) 4
Number of protected poles 4
Rated current 80 A
Rated voltage 400 V
Rated insulation voltage Ui 500 V
Rated impulse withstand voltage Uimp 6 kV
Voltage type AC
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V 50 kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V 25 kA
Frequency 50-60 Hz
Flush-mounted installation Yes
Concurrently switching neutral conductor Yes
Pollution degree 3
Additional equipment possible Yes
Width in number of modular spacings 6
Degree of protection (IP) IP20
Ambient temperature during operating -25-70 °C
Connectable conductor cross section multi-wired 6-50 mm²
Connectable conductor cross section solid-core 6-70 mm²
Explosion-proof No
Width 106.8 mm
Height 127.5 mm
Depth 79.2 mm
Degree of impact strength (IK) IK02

Storage temperature -40-70 °C
Nominal voltage 360-440 V
Electric supplying direction By the top or bottom
Terminal marking indication No
Colour Grey
RAL-number 7035
Halogen free Yes
Connection type Screwed terminal , Cable
Label space/information surface Yes
Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficien?? ?i calitate superioar?.
Pret: 1.278,55 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/disjunctor-dx3-4p-400v-80a-25ka-curba-b-6m