



LEGRAND* DISJUNCTOR MAGNETIC SIMPLU DX³-MA - 4P - 40 A - 50 KA - CURBA MA - 6M

Descoper? Disjunctor magnetic simplu DX³-MA - 4P - 40 A - 50 kA - curb? MA - 6M din categoria Sigurante automate - Tetrapolare, un produs cu codul 410264. Acesta ofer? caracteristici excelente: Built-in depth 47 mm

Release characteristic MA

Number of poles (total) 4

Number of protected poles 4

Rated current 40 A

Rated voltage 400 V

Rated insulation voltage U_i 500 V

Rated impulse withstand voltage U_{imp} 6 kV

Voltage type AC

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V 100 kA

Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V 50 kA

Frequency 50-60 Hz

Flush-mounted installation Yes

Concurrently switching neutral conductor Yes

Pollution degree 3

Additional equipment possible Yes

Width in number of modular spacings 6

Degree of protection (IP) IP20

Ambient temperature during operating -25-70 °C

Connectable conductor cross section multi-wired 1.5-35 mm²

Connectable conductor cross section solid-core 1.5-50 mm²

Explosion-proof No

Width 106.8 mm

Height 127.5 mm

Depth 79.2 mm
Degree of impact strength (IK) IK02
Storage temperature -40-70 °C
Nominal voltage 360-440 V
Electric supplying direction By the top or bottom
Terminal marking indication No
Colour Grey
RAL-number 7035
Halogen free Yes
Connection type Screwed terminal , Cable
Label space/information surface Yes
Mounting method DIN rail. Ideal pentru proiectele tale, asigurand eficienta si calitate superioara.
Pret: 1.124,41 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/disjunctor-magnetic-simplu-dx3-ma-4p-40-a-50-ka-curba-ma-6m>